

Solar Control



Constructie | Composition | Konstruktion | Construction

Buitenblad	
Exterieur	5T
Außen	
Outer pane	
Verdeler	0,3 Vacuüm
SZR	0,3 Vakuum
Intercalaire	0,3 Sous-vide
Spacer	0,3 vacuum
Binnenblad	
Intérieur	5T
Innen	
Inner Pane	

Specificaties | Spécifications | Spezifikationen | Specifications

	LTA TL LT LT	45-47	Lichttransmissie Transmission Lumineuse Lichttransmission Light transmission
EN410:2011	BLR RLE Lra ELR	15	Buiten lichtreflectie Réflexion Lumineuse Extérieure Lichtreflexion außen External light reflection
	LR (binnen) RLI Lri ILR	17	Binnen lichtreflectie Réflexion lumineuse Intérieure Lichtreflexion innen Internal light reflection
	G-waarde Valeur G G-wert G-value	0,29	Zontoetredingsfactor Facteur Solaire Gesamtenergiedurchlassgrad Solar factor
	U-waarde Valeur U U-Wert U-value	0,50	Isolatiewaarde Valeur d'isolation Dämmwert Insulation value
EN ISO 10140-1/2 EN ISO 717-1	RW (C ; Ctr) dB	36 (-2;-3)	Geluidsdemping Réduction du bruit Lärminderung Sound insulation

*U-waarde gebaseerd op EN674: ISO 19916-1
TÜV Rheinland, 2025.

*Valeur U basée sur EN674: ISO 19916-1
TÜV Rheinland, 2025.

*U-value based on EN674: ISO 19916-1
TÜV Rheinland, 2025.

* U-Wert basierend auf EN674: ISO 19916-1
TÜV Rheinland, 2025.



Netherlands

www.bengglas.nl
info@bengproducts.nl
+31 (0) 13 534 22 26

Belgium

www.bengglas.be
info@bengproducts.be
+32 (0) 19 60 08 31

